

SUSPENSION SETUP

RAZE CARBON RR TRAIL

Fork: Fox 36 29 Float GRIPX2 Factory Kashima, 150mm

Follow Fox 36 Float GRIP2 Factory Kashima recommended settings on the bottom right back side of the casting. Mondraker recommended Fox 36 Float GRIPX2 Factory Kashima fork settings based on rider weight and Trail application:

SAG		RECOMMENDED SETTING			
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED			
lbs / kg	psi	HSR	LSR	HSC	LSC
<121-128lbs / <55-58 kg	55	9	16	7	16
129,8-136,4lbs / 59-62 kg	59	8-7	15	7	15
138,6-145,2lbs / 63-66 kg	63	8-7	14	7-6	14
147,4-154lbs / 67-70 kg	67	7-6	13	7-6	13
156,2-162,8lbs / 71-74 kg	71	7-6	12	6-5	12
165-171,6lbs / 75-78 kg	75	6-5	11	6-5	11
173,8-180,4lbs / 79-82 kg	79	6-5	10	5-4	10
182,6-189,2lbs / 83-86 kg	83	5-4	9	5-4	9
191,4-198lbs / 87-90 kg	87	5-4	8	4-3	8
200,2-206,8lbs / 91-94 kg	91	4-3	7	4-3	7
209-215,6lbs / 95-98 kg	95	4-3	6	3-2	6
217,8-224,4lbs / 99-102 kg	99	3-2	5	3-2	5
226,6-233,2lbs / 103-106 kg	103	3-2	4	2-1	4
235,4-242lbs / 107-110 kg	107	2-1	3	2-1	3
244,2-250,8lbs / 111-114 kg	111	2-1	2	1	2
>253-319lbs / >115-145 kg	115	1	1	1	1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox Float-X Factory Kashima EVOL

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	115	10	12
129,8-136,4lbs / 59-62 kg	122	10	12
138,6-145,2lbs / 63-66 kg	129	10-9	12
147,4-154lbs / 67-70 kg	136	9	11
156,2-162,8lbs / 71-74 kg	143	9-8	11
165-171,6lbs / 75-78 kg	150	8	10
173,8-180,4lbs / 79-82 kg	157	8-7	9
182,6-189,2lbs / 83-86 kg	164	7	8
191,4-198lbs / 87-90 kg	171	7-6	7
200,2-206,8lbs / 91-94 kg	178	6	6
209-215,6lbs / 95-98 kg	185	6-5	5
217,8-224,4lbs / 99-102 kg	192	5	4
226,6-233,2lbs / 103-106 kg	199	5-4	3
235,4-242lbs / 107-110 kg	206	4	2
244,2-250,8lbs / 111-114 kg	213	3	1
>253-319lbs / >115-145 kg	220	2	1

*Settings based on Trail application and 30-35% recommended sag