

SUSPENSION SETUP

CRAFTY S E-MTB ENDURO

Fork: RockShox ZEB Base 29, Delta RC, 160mm

Follow RockShox ZEB Base recommended settings on the bottom right back side of the casting. Mondraker recommended RockShox ZEB Base fork settings based on rider weight and E-MTB Enduro application:

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	50	-2	14
129,8-136,4lbs / 59-62 kg	54	-2	13
138,6-145,2lbs / 63-66 kg	58	-2	12
147,4-154lbs / 67-70 kg	62	-1	11
156,2-162,8lbs / 71-74 kg	66	-1	10
165-171,6lbs / 75-78 kg	70	-1	10-9
173,8-180,4lbs / 79-82 kg	74	0	9
182,6-189,2lbs / 83-86 kg	78	0	9-8
191,4-198lbs / 87-90 kg	82	0	8
200,2-206,8lbs / 91-94 kg	86	0	8-7
209-215,6lbs / 95-98 kg	90	1	7
217,8-224,4lbs / 99-102 kg	94	1	7-6
226,6-233,2lbs / 103-106 kg	98	1	6
235,4-242lbs / 107-110 kg	102	2	6-5
244,2-250,8lbs / 111-114 kg	106	2	5
>253-319lbs / >115-145 kg	110	2	5

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: RockShox Super Deluxe Base

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	175	open	12
129,8-136,4lbs / 59-62 kg	185	open	11
138,6-145,2lbs / 63-66 kg	195	open	10
147,4-154lbs / 67-70 kg	205	open	9
156,2-162,8lbs / 71-74 kg	215	open	8
165-171,6lbs / 75-78 kg	225	open	7
173,8-180,4lbs / 79-82 kg	235	open	6
182,6-189,2lbs / 83-86 kg	245	open	5
191,4-198lbs / 87-90 kg	255	open	5-4
200,2-206,8lbs / 91-94 kg	265	open	4
209-215,6lbs / 95-98 kg	275	open	4-3
217,8-224,4lbs / 99-102 kg	285	open	3
226,6-233,2lbs / 103-106 kg	295	open	3-2
235,4-242lbs / 107-110 kg	305	open	2
244,2-250,8lbs / 111-114 kg	315	open	2-1
>253-319lbs / >115-145 kg	325	open	1

*Settings based on Enduro application and 30-35% recommended sag